



802 WD - PROFESSIONAL WET & DRY



BUILDING AND CONSTRUCTION



WINE



CLEANING CONTRACTORS



VEHICLE - TRANSPORT CLEANING



- ✓ Two powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ PPL filter for protection of motors from liquids and foam

- ✓ Discharge hose for liquids
- ✓ Accessory kit as standard



SUCTION UNIT

| | | |
|---------------------------|-------------------|----------|
| Voltage | V - Hz | 230 - 50 |
| Power | kW | 2,3 |
| Max waterlift | mmH2O | 2.500 |
| Max air flow | m ³ /h | 360 |
| Suction inlet | mm | 80 |
| Noise level (EN ISO 3744) | dB(A) | 76 |



FILTER UNIT

| | | |
|-----------------------|---------------------|-------------------|
| Filter Type | | Bag |
| Surface - Diameter | cm ² -mm | 8.000 - 420 |
| Material - Efficiency | IEC 60335-2-69 | Kit wet + Kit dry |
| Cleaning system | | Manual |



COLLECTION UNIT

| | | |
|------------------|-----|----------------|
| Discharge system | | Discharge hose |
| Capacity | lt. | 80 |



VOLUME

| | | |
|------------|----|------------|
| Dimensions | cm | 53x59x106h |
| Weight | kg | 40 |



SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.

A propylene filter for liquids is installed upstream. This filter guarantees the efficient filtration of the vacuumed oil; an additional plastic foam filter prevents most of the liquid mist from getting to the motor.



COLLECTION UNIT

The vacuum cleaner is mounted on a solid steel trolley, provided with a support for hoses when not used, and equipped with oil proof wheels and braking castors.



OPTIONALS

✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST