

Comfort XS-R1 Essential











Equipped with:

- Capable to work for the maintenance and deep cleaning of large areas (up to 3.700 m²) with a very important reduction of cost of cleaning
- More than 50 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Compact size (810 mm)
- Stability even when fully loaded, front independent wheeldrive with tight steering radius
- Recovery tank control window for cleaning and easy ordinary maintenance
- Easy access to electrical components
- Automatic device that stops brushes and detergent water outflow when the machine is stationary
- Self-levelling brushes.
- New control panel
- Automatic brush release
- Separate eco mode for brush and suction

* New, standard on machines starting from 2022, compatible with all previous machine models

	Comfort XS-R1 75 Essential	Comfort XS-R1 85 Essential
code	8.574.5001	8.574.5003
power supply	24V	24V
scrubbing/squeegee width	750/900 mm	850/1000 mm
max working capacity	4350 m ² /h	5000 m ² /h
solution tank capacity	110 l/29.05 gal	110 l/29.05 gal
recovery tank capacity	130-155 l/34.35-40.95 gal	130-155 I/34.35-40.95 gal
traction type/power	front motorwheel/600 W	front motorwheel/600 W
RPM/pressure on the brushes	170/50 kg/110.23 lbs	170/50 kg/110.23 lbs
brush motor power	2 x 400 W	2 x 400 W
max gradient empty/full tank	13%/10%	13%/10%
depression/vacuum motor	1300 mmH ₂ O/400W	1300 mmH ₂ O/400W
dimensions/weight	146x81x138 cm/184 kg	146x87x138 cm/187 kg

STANDARD EQUIPMENT



Comfort XS-R1 75

• 2 x 5.511.2218 PP brush Ø 360 mm - 14"



Comfort XS-R1 85

• 2 x 5.511.2255 PP brush Ø 430 mm - 17"





Front squeegee blade L.925 mm Shore 40 Th. 3 mm

• 4.508.0605

Rear squeegee blade L.1015 mm Shore 30 Th. 4 mm

Comfort XS-R1 85

• 4.508.1196

Front squeegee blade L.1027 mm Shore 40 Th. 3 mm

• 4.508.1195


Rear squeegee blade L.1150 mm Shore 33 Th. 4 mm

RIDE ON



The detergent water tank serves as battery compartment, allowing the housing of great capacity batteries granting continuous working time up. Large capacity shock and acid proof polyethylene tank (110 l) improves productivity avoiding frequent refilling and idle time.

Simple and intuitive controls reduce operator's training time. Easy mechanical brush plate and squeegee lifting system, for low maintenance costs. The enbloc brush plate apply a very high pressure (50 kg) to the floor, strongly and deeply removing any kind of dirt.





New control panel with digital controls and display. Digital display: with hour meter, battery charge level indicator, empty water tank level indicator. forward/reverse traction indicator. Speed control adjustment, horn, suction motor switch with delayed switch-off, brush plate lifting/ lowering selector switch, brush motor switch.

The ergonomic and comfortable shape of the machine allows the operator to work effortless for a long time, improving productivity.



OPTIONAL



• 4 x 0.107.0004 Tubular battery Pb-acid 6V 180Ah C5



• 4 x 0.107.0072 GEL Battery 6 MFP 180 6V 180Ah C5



• 0.108.0080 Battery Charger 24V 30A 220-240/50-6



• 5.511.1641 On-board Battery charger kit - 24V - 20A



- 4.508.0901 Polyurethane front blade L.925 TH.3 Sh.40
- 4.508.0900 Polyurethane rear blade L.1015 TH.4 Sh.40
- 4.508.1251 Polyurethane front blade L.1027 TH.3 • 4.508.1252 Polyurethane rear blade L.1150 TH.4



•2x 5.511.2219 Tynex brush Ø 360 mm-14" •2x 5.511.2220 PP 0,3 brush Ø 360 mm-14" •2x 5.511.2221

PES brush Ø 360 mm - 14"

•2x 5.511.2229 Tynex brush Ø 430 mm-17" •2x 5.511.2230 PP 0,3 brush Ø 430 mm-17" •2x 5.511.2231 PES brush Ø 430 mm - 17"



- •2x 5 511 2252 EWU pad driver Ø 380 mm-15"
- •2x 5.511.2232 EWU pad driver Ø 430 mm-17"



- 6.508.0143 Ø 380 mm -15"- beige (5 pcs.)
- 6.508.0144 Ø 380 mm -15"- green (5 pcs.)
- 6.508.0141 Ø 380 mm -15"- black (5 pcs.)
- 6.508.0032 Ø 430 mm -
- 17"- beige (5 pcs.) • 6.508.0039 - Ø 430 mm -
- 17"- green (5 pcs.)
- 6.508.0046 Ø 430 mm -17"- black (5 pcs.)