

Lena E



CRANKSHAFT



Equipped with:

- Sturdy frame painted with anti-corrosive treatment
- Stainless steel cover panels
- **Low voltage (24V) control panel with start-delta system**
- Handy lance and gun storage
- High filtering capacity cartridge suction filter
- Ø 300 industrial wheels with brake
- Electric motor (1450 rpm) 20,25 and 30 HP
- TW 500 Premium pumps /TW
- Motor-pump coupling by means of a flexible joint
- Automatic unloader valve with external bypass and gradual pressure restoring (on 5018 and 5021 models)
- Overheating thermostatic valve
- Low voltage (24V) start-up panel (star-delta)
- Remote switch and motor cut-out with thermal relay
- Emergency stop button
- **Hour counter**
- Hose reel with 20 mt hose can be mounted on request (cod. 0.966.0035)

On request 60Hz version

	Lena 5015 E LP	Lena 5018 E LP	Lena 5021 E LP	Lena 2042 E LP
code	0.066.0008	0.066.0009	0.066.0010	0.066.0055
operat. pressure	500 bar-7252 psi	500 bar-7252 psi	500 bar-7252 psi	200 bar-2900 psi
delivery rate	900 l/h-3.96 GPM	1080 l/h-4.75 GPM	1260 l/h-5.55 GPM	2520 l/h-11.09 GPM
abs. power/voltage	15000W - 380/415V~50Hz 3 ph	18500W - 380/415V~50Hz 3 ph	23000W - 380/415V~50Hz 3 ph	18500W - 380/415V~50Hz 3 ph
motor/pump type/RPM	TW500/1400 RPM	TW500/1400 RPM	TW500/1400 RPM	TW/1400 RPM
max. water inlet temperature	60 °C	60 °C	60 °C	60 °C
dimension/weight	118,5x74x100 cm/215 Kg - 473 lbs	118,5x74x100 cm/260 Kg - 496 lbs	118,5x74x100 cm/285 Kg - 507 lbs	118,5x74x100 cm/225 Kg - 496 lbs

STANDARD EQUIPMENT

- 0.966.0005 Gun ML 960 with quick coupling M24-M24 (mod.5015/5018/2042)
- 0.966.0006 Gun ML 710 with quick coupling M24-M24 (mod.5021)
- 0.966.0009 S/S Lance 500 bar L50 (mod.5015/5018/2042)
- 0.966.0010 S/S Lance 500 bar L70 (mod.5021)
- 0.966.0038 Nozzle type 028 (mod. 5015)
- 0.966.0039 Nozzle type 035 (mod. 5018)
- 0.966.0040 Nozzle type 040 (mod. 5021)
- 3.103.0207 Nozzle type 12 (mod. 2042)
- 0.966.0013 High pressure hose 10 m
- 0.966.0012 High pressure hose 10 m (mod. 2042)
- Power cable 5 m

Optional:

- Rotax lance
 - 0.966.0016 (mod. 5015)
 - 0.966.0017 (mod. 5018)
 - 0.966.0018 (mod. 5021)
 - for model 2042: on request
- Pipe cleaning hose 25 m.
 - 0.966.0022 (mod. 5015)
 - 0.966.0023 (mod. 5018/5021)
 - for model 2042: on request
- Extension hose 20 m.
 - 0.966.0026
- Sand-blasting lance 500 bar
 - 0.966.0030 (mod. 5015)
 - 0.966.0031 (mod. 5018/5021)
 - for model 2042: on request
- 7.197.0515 Apron